Philips Firewire cable

6-Pinm / 4-Pin M connectors

SWR1231





Connect on the go

Connect to camcorders, scanners and other imaging devices while traveling.

Ideal for travel

- Eliminates tangles for easy cable management
- Retractable cable for easy storage

Enjoy extended durability

· Molded ends for extended durability

Fast data transfer

• 400 Mbps transfer speed

Meets your specific connection requirements

• Meets IEEE 1394a specifications



Firewire cable 6-Pinm / 4-Pin M connectors I m

Specifications

Connectivity

Type of cable: Retractable Firewire Cable 4-pin Male / 6-pin Male

Dimensions

· Cable length: 100 cm

Packaging

• EAN/UPC/GTIN: 87 10895 98343 3

Quantity: ILength: 21 cm • Width: 14 cm

• Height: 2 cm

Gross Weight: 0.06 kg

• Net Weight: 0.026 kg

• Tare Weight: 0.034 kg

Inner Carton

• EAN/UPC/GTIN: 87 10895 99156 8

• Quantity: 4

Length (cm): 22 cm Width (cm): 8 cm

Height (cm): 15 cm

• Gross weight: 0.308 kg

 Net weight: 0.244 kg • Tare weight: 0.064 kg

Outer Carton

• EAN/UPC/GTIN: 87 10895 99157 5

Quantity: 12

Length (cm): 25 cm

Width (cm): 24 cm

Height (cm): 18 cm • Gross weight: 1.182 kg

Net weight: 0.926 kg

• Tare weight: 0.256 kg

Product highlights

Meets IEEE 1394a specification

Meets mandated standard for data transmission.

Eliminates tangles

The spring-loaded retractable device facilitates easy mobility when traveling by allowing you to select exactly the length of cable you need and storing the rest on an internal reel.

400 Mbps transfer speed

400 Mbps transfer speed meets the IEEE 1394a standard.



Issue date 2008-09-02

Version: I.4.10

© 2008 Koninklijke Philips Electronics N.V.

All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

12 NC: 9082 100 09072 EAN: 87 10895 98343 3

www.philips.com